




Rocburn NSHEV Flat Roof
Louver Ventilator



NSHEV conforms to
NF EN 12101-2 and
NFS 61 937-1.

NSHEV installed on the roof.
The vents can be used on simplest
projects as well as more architectural

DESCRIPTION

- The louver ventilator is a complete NSHEV (Natural Smoke and Heat Exhaust Ventilators) which has its own mechanisms.
- Frame profiles are available as standards to be integrated in all kind of structures.
- Its different dimensions allow a tailor-made manufacturing which respects architectural wefts and modules.
- Its aesthetic allows to be integrated:
 - on roof,
 - for any RAL paint or anodised finish.
- CE fix windshields are mandatory on the roof.

REGULATION

- A complete NSHEV (Natural Smoke and Heat Exhaust Ventilator) conforms to NF EN 12101-2 and NFS 61 937-1 norms.

PROFILES

- Extruded aluminium frame to fit any type of roof structure.
- Various types of profiles (F, G, J) in accordance with roofing type or glazing.

PERFORMANCES

- Smoke vent conforms to NF EN 12101-2 and NFS 61 937-1 norms.
- 1200 J resistance.
- Classification air/water/wind: in process.
- Reliability: Re 1,000 and Re 10,000.
- Aerodynamic value: Cv from 0.62 without upstand and 0.67 with upstand.
- Snow load (SL250 and SL500).
- Ug: from 1.32 W m²/°K* for insulated blades.



* Test reports on demand.

Ask about our other smoke vent equipment







Rocburn NSHEV Flat Roof Louver Ventilator



Principle of installation frame C



Principle of installation on upstand with frame C

Tailor-made manufacturing:

- Throat width: mini 500, maxi 2,000 mm.
- Throat height: mini 800, maxi 3,500 mm.
- SGO: mini 1 m², maxi 7 m² (CE mark).

INFILL

- Standard (No insulated) aluminium blade or thermal insulation with anodised or mill finish.
- Acoustic insulation option.
- Ug: 1,32 W/m² °C (for insulated blade).
- Acoustic insulation: Rw of 18 dB.

TYPES OF CONTROLS

By remote controlled:

- Electrical
- Pneumatic
- Mechanical

OPTIONS

- Insulated (bituminous) upstand (for installation on multilayered roof).
- Standard upstand without insulation.
- O/c switch (safety option)
- Thermal release (70, 100, 140 and 180°, compulsory).

INSTALLATION

- For roof installation to be integrated on upstand

Ask about our other smoke vent equipment

