

C260

Dual push points chain actuator
Thrust force 600N
Max stroke 600mm

PRODUCT DESCRIPTION

Electric actuator Topp model C260 with 2 double-link chains, in an elegant die-cast aluminium profile, with custom-made length from 1530 mm to 4000 mm, complete with brackets and accessories for top and bottom hung windows. Operation at 230V~50Hz. Max. thrust force 600N. Max. stroke 600 mm. Electronic end of stroke in closing by current absorption control. CE marked device.



Tailored profile lengths according to the window frame width (International patent).



Special hooking of chain to window to guarantee very high resistance with a long stroke even on top hung windows.



Innovatory and original design.



TECHNICAL SPECIFICATIONS

C260 230V

Power supply voltage	230V ~ 50Hz
Max applicable load in thrust	600 N
Max applicable load in traction	600 N
Stroke	600 mm
Absorbed current	0,4A
Idle translation speed	13 mm/s
Duration of the idle stroke	46 s
Double insulated	YES
Service type	S2 of 4 min
Operating temperature	- 5°C + 50°C
Protection Class	IP 30
Stroke end regulation in closure	not necessary
Parallel connection option	YES
Stroke end	Electronic in opening, by amperometric absorption in closing

C260 dual push points actuator (profile's length: 1530 - 2000 mm), stroke 600 mm application on top hung windows

3E15# Dual push points actuator C260 230 V

C260 dual push points actuator (profile's length: 2010 - 2500 mm), stroke 600 mm application on top hung windows

3E15# Dual push points actuator C260 230 V

C260 dual push points actuator (profile's length: 2510 - 3000 mm), stroke 600 mm application on top hung windows

3E15# Dual push points actuator C260 230 V

C260 dual push points actuator (profile's length: 3010 - 4000 mm), stroke 600 mm application on top hung windows

3E15# Dual push points actuator C260 230 V

Description of the standard pattern (profile's length: 1500 - 2000 mm), stroke 600 mm application on top hung windows

3E15# Dual push points actuator C260 230 V
 Frontal bracket for top hung windows (2 pcs)
 Clamps set for top hung brackets (2 pcs)
 Hooking device to the frame for top-hung application - black (2 pcs)

Note: Part Numbers will be assigned according to the required profile's length.

Accessories and spare parts

3A5005 Clamps for top hung windows
 3A5006 Clamps for bottom hung windows
 1A5822 Slim frontal bracket for top hung windows (window opening min. 400mm)
 1A5823 Bracket for vertical mounting (window opening >350mm)
 1A5829 Bracket for bottom-hung outward opening application (window opening 550mm)
 1A5832 Bracket for installation on bottom hung windows
 1A5800 Fallback bracket for bottom hung windows
 3E3100 Hooking device to the frame for top-hung application - black

