



WMU 836 03

WAB 836B

WAB 836E

WMU 836 03

Chain actuator for VELUX window



Natural
ventilation



Smoke
ventilation

2.20

Application

- chain actuator for VELUX windows
- for smoke and comfort ventilation
- chain stroke 600mm

24V DC chain actuator for VELUX top hung, tilt-and-swing windows GPL and GPU from size M06 and VK from size 045.

The housing and the chain is protected against corrosion.

Special technical features

- built-in electronic load switch off
- chain stroke 600mm
- aluminium housing with stainless steel chain

WMU 836 03

Chain actuator for VELUX window

Technical specifications	
Force (pressure/tractive)	150N / 300N
Chain stroke	600mm
Opening speed	11mm/s (programmable up to 14mm/s)
Nominal voltage	24V DC (max. 25% ripple)
Voltage	20 - 36V DC
Open-circuit voltage	max. 36V DC
Current consumption	max. 1A
Operating conditions	-5°C - +74°C, max. 90% relative humidity (not condensing)
Switch-on-duration	ED 40% (max. 4min. per 10min.)
Material	anodised aluminium housing with stainless steel chain
Colour	anodized aluminium (EV1)
Size	650 x 34 x 47mm (W x H x D)
Weight	2.6kg
IP rating	IP32
Fire test	testet according to DIN 18232-3, part 3.6 (30 min./300°)
Life span	tested with 10,000 opening and closing movements
Delivery includes	actuator with 2m cable, chain bracket WAB 836E, actuator bracket WAB 836B 01 and cover
Note	we reserve the right to make technical changes.

Item	Item no.
Chain actuator for VELUX window	WMU 836 03

